

205 - TEAK OIL

TECHNICAL DATA SHEET | NORDICARE

Wood care

TEAK OIL is an oil for the treatment and maintenance of oil-treated wooden surfaces such as teak, rosewood and mahogany. The oil enhances the natural colour and grain of the wood and helps maintain the surface by reducing drying under normal use conditions.

Key Benefits

- Refreshes the visual depth and warmth of oil-treated hardwood.
- Highlights the natural wood grain without creating a heavy lacquer-like film.
- Simple wipe-on application for regular furniture maintenance.
- Suitable for teak, rosewood and mahogany surfaces.

Application area

For oil-treated indoor wooden furniture and hardwood surfaces. Especially relevant for teak, rosewood and mahogany. Always test on a small, inconspicuous area.

Instructions

Ensure that the surface is clean, dry and free from dust, grease and loose residues before treatment. Apply in a thin even layer with a soft cloth in the direction of the wood grain. Allow the oil to penetrate and wipe off excess oil after approximately 2 hours.

Do not leave excess oil to dry on the surface, this may result in a sticky or uneven finish. Repeat the treatment if the wood appears very dry or uneven.



Conditioning

250 ml (12 units/box)
500 ml (12 units/box)

Document control

Document no.: TDS-205
Product: Teak Oil
Version: 01
Revision date: 07.07.2026
Prepared by: Technical Department

Declaration

Contains: Drying oils, paraffinic oil, aliphatic hydrocarbons and antioxidants.

Safety information

DANGER

May be fatal if swallowed and enters airways.

Keep out of reach of children. Use only in well-ventilated areas and avoid inhalation of vapours.

IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting.

Used cloths may self-ignite. After use, soak cloths with water and dispose of them in an airtight plastic bag or wrapped tightly in aluminium foil.